

Rev: B
Page: 1 of 4
Date: 01/25/07

F 7.3.29

Form

	I. PRODUCT I	DENTIFICATION -			
TRADE NAME (as labeled): LAT	TICRETE® 38 Acrylic A	dmix			
CHEMICAL FAMILY: Acrylic Lat	ex				
MANUFACTURER'S NAME:	1 Laticrete Park,	LATICRETE INTERNATIONAL, INC. 1 Laticrete Park, N. Bethany, CT 06524-3423 USA		Reviewed & Approved By: <u>Steven 3: 7tne</u> Steven B. Fine	
Phone number for additional info	ormation: (203) 393-00	010		ch Chemist/Safety Officer	
Date prepared or revised: 2/08		of preparer: SB. F US INGREDIENTS			
CHEMICAL NAMES CAS NUMBE None		ACGIH TLV	OSHA PEL	OTHER (SPECIFY)	
N/A = Not applicable or availal	ble				
SYMPTOMS OF OVEREXPOS Effects) N/A					
SIGNS AND SYMPTOMS OF E. Inhaled: No adverse effects are	`	,			
Contact with skin or eyes: Sho may cause slight, temporary eye		to cause significar	nt skin irritation.	Eye contact	
Absorbed through skin: Skin at	osorption is unlikely du	e to physical prope	erties		
Swallowed: Single dose oral tincidental to industrial exposure SUSPECTED CANCER AGENT x NO: This product's ingred	?		ds anticipated fi	rom ingestion	
YES: Federal OSHA	NTP	IARC			



F 7.3.29

Rev: B
Page: 2 of 4
Date: 01/25/07

Form

Eye Contact: Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. Skin Contact: Wash off in flowing water or shower Inhaled: No adverse effects Swallowed No adverse effects anticipated by this route of exposure incidental to proper industrial handling	IV. FIRST AID: EN	MERGENCY PROCEDURES	
Inhaled: No adverse effects anticipated by this route of exposure incidental to proper industrial handling	Eye Contact: Hold eyelids apart and in	mmediately flush eyes with plenty of water for at least	
Swallowed No adverse effects anticipated by this route of exposure incidental to proper industrial handling	Skin Contact: Wash off in flowing water of	or shower	
Flash Point method): Non-flammable or combustible in liquid form Auto ignition temperature,°F: N/A Flammable limits in air, volume %: Lower (LEL) Upper (UEL) Fire extinguishing materials: x water spray carbon dioxide other: foam dry chemical Special fire fighting procedures: N/A Unusual fire and explosion hazards: As latex, material is not combustible; however, the dried resin is combustible similar to wood. Burning dry resin emits dense, black smoke.	handling		strial
Flammable limits in air, volume %: Lower (LEL) Upper (UEL) Fire extinguishing materials: x water spray carbon dioxide other: dry chemical Special fire fighting procedures: N/A Unusual fire and explosion hazards: As latex, material is not combustible; however, the dried resin is combustible similar to wood. Burning dry resin emits dense, black smoke.	Flash Point method): Non-flammable or of		
x water spray carbon dioxide other: foam dry chemical Special fire fighting procedures: N/A Unusual fire and explosion hazards: As latex, material is not combustible; however, the dried resin is combustible similar to wood. Burning dry resin emits dense, black smoke.	Flammable limits in air, volume %:	Lower (LEL) Upper (UEL)	
Unusual fire and explosion hazards: As latex, material is not combustible; however, the dried resin is combustible similar to wood. Burning dry resin emits dense, black smoke.	<u>x</u> water spray	carbon dioxide other: dry chemical	
combustible similar to wood. Burning dry resin emits dense, black smoke.	Special fire fighting procedures: N/A		
Spill response procedures (include employee protection measures): Flush area with water immediately. Avoid unnecessary exposure and contact. Wear safety glasses and impervious gloves. Preparing wastes for disposal (container types, neutralization, etc.): Soak up with absorbent materials. Store in pails or drums. Bury in an approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water. NOTE: Dispose of all wastes in accordance with federal, state and local regulations.	• • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·	in is
Immediately. Avoid unnecessary exposure and contact. Wear safety glasses and impervious gloves. Preparing wastes for disposal (container types, neutralization, etc.): Soak up with absorbent materials. Store in pails or drums. Bury in an approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water. NOTE: Dispose of all wastes in accordance with federal, state and local regulations.	VI. SPILL, LE	AK, AND DISPOSAL PROCEDURES	
materials. Store in pails or drums. Bury in an approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water. NOTE: Dispose of all wastes in accordance with federal, state and local regulations.			
VII. Handling and Storage	materials. Store in pails or drums. Bury	y in an approved landfill or burn solid wastes in an adequ	
	NOTE: Dispose of all wastes in accordar	nce with federal, state and local regulations.	



Rev: B
Page: 3 of 4
Date: 01/25/07

F 7.3.29

Form

•	ols and Personal Protectional ventilation should be sufficient for most conditions	
Respiratory protection (type): No respiratory p maintained	rotection should be needed if good ventilation is	
Eye protection (type): Use chemical goggles or sa	afety glasses	
Gloves (specify material): Impervious gloves, viny	l or rubber	
Other clothing and equipment: Wear clean, long-s	sleeved, body-covering clothing	
Work practices, hygienic practices: Maintain good	housekeeping standards	
Other handling and storage requirements: N/A		
Protective measures during maintenance of conta	minated equipment: See above.	
IX. PHYSICA	AL PROPERTIES	
Vapor density (air=1): N/A	Melting point or range,°F: N/A	
Specific gravity: 1.00	Boiling point or range, °F: 212	
Solubility in water: Emulsion Vapor pressure, mmHg at 20°C: N/A Appearance and odor: White liquid, slight odor HOW TO DETECT THIS SUBSTANCE (warning mist):	Evaporation rate (butyl acetate = 1): N/A g properties of substance as a gas, vapor, dust, o	
X. REAC	TIVITY DATA	
Stability:	x Stable Unstable	
Conditions to avoid: May coagulate if frozen at 32	2°F	
Incompatibility (materials to avoid): N/A		
Hazardous decomposition products (including correaction with other materials). If dried resin is bur gases (carbon monoxide and hydrocarbons	nbustion products): (from burning, heating, or ned, produces a dense black smoke and noxious	
Hazardous polymerization: Ma	y occurx Will not occur	
Conditions to avoid: N/A		



Form F 7.3.29

Rev: B
Page: 4 of 4
Date: 01/25/07

N/A	XI. Toxicology Information
 N/A	XII. Ecological Information
Dispose in compliance with local,	XIII. Disposal Informationstate, and federal regulations.
No special labeling or transportati	XIV. Transport Informationon placarding is required.
All ingredients are listed on the U.	XV. Regulatory InformationS. EPA TSCA inventory of chemical substances.
This information is furnished witho	XVI Other Information out warranty, representation, inducement or license of any kind; est of our knowledge, or obtained from sources believed by us to be